



Echo

Environmental

GREENGUARD Gold Certified
 LBC Red List Free
 REACH Compliant
 RoHS Compliant
 Healthier Hospitals Compliant
 Recycled content
 No PFAS, fluorocarbons or perfluorinated compounds
 No added antimicrobials



47% FR Polyester, 46% Post Consumer Recycled Polyester, 7% Polyester

12.11 oz./lin. yd. ± 1.0 oz.

72 inches

Horizontal: 37 inches, Vertical: 39.75 inches, shown railroaded, directional, reversible

60 yards

Made in the USA

Warp: 263 lbs. min., Fill: 244 lbs. min.

Warp: 25 lbs. min., Fill: 56 lbs. min.

Warp: 78 lbs. min., Fill: 108 lbs. min.

Class 4.0 min.

60 Hours, Class 4.0

Dry: Class 3.0, Wet: Class 4.0

Passed

Passed

Specifications - inches

Content

Weight

Width

Repeat

Roll Size

Performance Characteristics

Break Strength ASTM D-5034

Tear Strength ASTM D-2261

Seam Slippage ASTM D-4034

Brush Pilling ASTM D-3511

Colorfastness to Light AATCC-16

Crocking AATCC-8

Flammability*

California Technical Bulletin 117-2013,
Section 1

NFPA 701 (Small Scale)